



SR No.	SIZE		SPEED R.P.M.	A	B	C	D
	INCHES	MM					
01	12	305	1450	515	165	350	1450
02	16	380	1450	515	165	350	1450
03	18	457	1450	515	165	350	1450
04	24	610	900	670	180	365	900
05	30	30	900	830	180	365	900

TYPE NO. : NF 42000
 CERT No.: ERTL (E) /TEST/N139/0085/11-07
 BIS CERT No. : CM/L-7892304
 CCEs Identification No. : P244814/9

TECHNICAL DATA

ENCLOSURE :

Ex d IIA IIB, AS PER IS:2148-2004/IEC60079-1(2001)
 & IS:13346-2004/IEC 60079-0(2000)

DEGREE OF PROTECTION :

IP-65 AS PER IS:12063-1987/IEC 60529-1989

AREA CLASSIFICATION :

Div/Zone 1 & 2, GAS GROUPS IIA IIB

MATERIAL OF CONSTRUCTION :

CAST IRON

RATING & TEMPRATURE CLASSIFICATION :

1/3 PHASE, 50 Hz. 1450/950 RPM T6

GASKET :

NEOPRENE

HARDWARE :

STAINLESS STEEL

FINISH :

LIGHT GREY EPOXY SHADE 631 AS PER IS:5.

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

3/4" ET x 1 No.

REV.	DATE	DRN BY	CHKD BY	APPRD BY	NATURE OF CHANGE
0	01.03.08	BKP	BKC	BKC	NA.

NEMA™ **NEMA SWITCH GEAR**

CLIENT :	P.O No. :	
CONSULTANT :	ITEM No. :	QTY : 1 Nos.
TITLE : FLP/WP FAN	DRG. No. : D2 / NF003 / 07	Sheet 1 of 1 SCALE : N.T.S.